

DATA SHEET

KP04 TYPE 'K' NEEDLE PROBE

Needle Probes - 1.5 mm Type 'K'

Description

This probe uses a small diameter needle for ease of use in confined spaces. It is suitable for semi-solid product.

Construction

Needle Probe 1.5mm Diameter by 60mm Long : Stainless Steel 316 (Food Grade)
2M curly polyurethane cable with moulded connector. Complete waterproof assembly.

Sensor Features

➤ **TOTAL ENCAPSULATION TECHNIQUE FOR MAXIMUM STRENGTH AND DURABILITY.**

This results in a solid handle as opposed to a hollow handle. This is particularly important as there is often damage to the handles caused by excess heat. With a hollow handle it is possible to puncture the outer plastic and damage the sensor irreparably.

➤ **WATERPROOF HANDLE**

Due to the total encapsulation method used, all TME probe handles are completely waterproof.

➤ **TOUGH PTFE CABLE**

- Polyurethane cables are used in place of the standard PVC for the following reasons :-
- Greater retractability
- Enhanced memory of its curl
- Non-Toxic
- Greater mechanical strength for durability
- 12 X 0.2mm wires used internally for greater strength.
- PTFE inner insulation for strength and retractability.

➤ **HIGH ACCURACY THERMOCOUPLE MATERIAL THROUGHOUT**

Type 'K' Thermocouple : Class I (±1.5°C ±0.25%)

➤ **POLYPROPYLENE HANDLES**

Polypropylene is an extremely tough and durable material, commonly used for milk crates, it has good low temperature performance and a relatively high melt temperature. It performs exceptionally well under chemical attack.

- **WIDE AMBIENT TEMPERATURE SPECIFICATION** : -30 TO 50 °C
- **TIME RESPONSE (96% of value in water)** : 1.6 Secs
- **MEASUREMENT RANGE** : -100 TO 280 °C

Cross-reference for compatible instruments

Suitable instruments for use with this probe

| TME PART No | DESCRIPTION | APPLICATION |
|-------------|---------------------------|--|
| MM2000 | SINGLE INPUT INSTRUMENT | HIGH ACCURACY TEMPERATURE MEASUREMENT |
| MM2010 | MAX / MIN HOLD INSTRUMENT | HIGH ACCURACY INSTRUMENT WITH MAX, MIN AND HOLD FEATURES |
| MM2020 | DIFFERENTIAL INSTRUMENT | DUAL INPUT INSTRUMENT FOR DIFFERENTIAL MEASUREMENTS |
| MM2030 | THERMOCOUPLE SIMULATOR | HIGH ACCURACY SIMULATOR WITH MEASUREMENT FACILITY |